

FLEXPOS

Q-POS 815 series

NEW Touch POS Terminal



CPU Supports	Intel® Pentium® 4 processor 2.8 GHz, FSB 533/400/333MHz
Mainboard	Flex-845P
Main Color	Black
LCD Size	15" TFT LCD 250 nits
Resolution	1024 x 768 XGA
Touch Screen	5-Wire resistive anti-glare surface treatment
Main Chipset	North Bridge: Intel® 845gv Chipset South Bridge: Intel® 82801 DB ICH4 Chipset
System Memory	- 1 x 184pin DDR RAM socket up to 1GB, supports PC 333/266/200, standard with 512M
Storage Devices	- 3.5" Hard Disk drive on pedestal, - 1 x Slim type CD-ROM on pedestal (option) - 1 x Multi Card Reader/Writer support SD/MMC/CF/SM/MS/Micro, USB Interface (option)
Graphics	Integrated VGA/LCD display controller, Video memory up to 64MB (share from system Memory) 2D/3D GUI engine, AGP 4X VGA, MPE-4/MPEG-2 playback
Watchdog Timer	256-level
LED Indicate	Power, HDD, LAN
Audio/ Speaker/Key Lock	ICH4 integrated audio with AC97 CODEC / Built-in stereo speakers on front panel/On front bezel
I/O Ports	- 6 x COM: COM 1/2/4: RS-232 in pin1/9 D-sub male, +5/+12V output, COM 5 for Normal; COM 3: Internal for Touch Screen Panel, COM 6: on board. - 6 x USB 2.0 (2 USB on rear bezel, 1 USB on front bezel, 3 x pin header) - Powered DC12V USB and DC24V USB Connector - 1 x Line-in, 1 x Line-out & 1 x Microphone-in - 1 x PS/2 Keyboard, 1 x PS/2 Mouse - 1 x RJ11 Cash Drawer 12V or 24V Solenoid type - 1 x LPT 25-pin DSUB Connector - 1 x RJ45 LAN (10/100 Base-T on board)
Construction	Inside: heavy-duty steel; Outside: ABS fire-proof resilient plastic (charcoal)
Temperature	Operating 0°C~45°C, Storage -20°C~60°C
Relative Humidity	10~90%, non-condensing
Tilt Angle	-10°~85° for both desk-top and wall mount without additional parts
Vibration	5~7Hz, 0.1" double amplitude displacement, 17~500Hz, 1.5G acceleration peak to peak
AC Power Supply	ATX 250W Power Supply, 100~240V
Operation System	WIN 2000/XP, XP Embedded, XP Pro. Embedded & WEPOS
Dimensions	15": 365 (W) x 351(H) x 343 (D) mm
Weight	8.1kgs
Safety & EMI	UL, FCC, CE
Options	- HYBRID Card Reader (IC Card + MSR Track 1/2/3 + i-Button) - Single Card Reader (Track 1/2/3) - Wireless LAN device IEEE 802.11g - 56K Modem Integrated (RS232 Interface) - Customer Display: VFD or LCD Pole Display



Goodson Imports Pty Ltd
142 Wicks Road
North Ryde NSW 2113
ABN 74 001 016 593

Ph 02-8875 4544
Fax 02-8875 4588
www.goodson.com.au