

IMPACT PRINTER

iDP3110/3111/CBM-910



iDP3110/3111



CBM-910

Features

- Palm size
- Lightweight
- Bit image graphic printing
- 2K bytes input buffer (CBM-910)
- Paper end sensor (CBM-910)
- Rechargeable internal battery (iDP3111)

Applications

- Receipt
- Ticket
- Credit/Debit
- Daily report
- Kitchen
- Delivery
- Portable (iDP3111)

Specifications

Model	iDP3110	iDP3111	CBM-910
Printing method	Serial dot impact		
Printing direction	Left to right		
Font	5 x 8 matrix		
Number of columns	24/40 columns		
Printing speed	24 col. = 2.5 lines/sec. 40 col. = 1.8 lines/sec.		
Character size (W x H)	24 col. = 2.4 x 1.62mm 40 col. = 2.4 x 1.08mm		
Line Spacing	Character = 3.52mm Graphic = 2.4mm		
Character pitch	24 col. = 1.98mm 40 col. = 1.19mm		
Line feed speed	5.0 lines/sec.		
Paper	57.5mm		
Interface	Parallel: Centronics Serial: RS-232C		
Input buffer	1 line		2K bytes
Paper end detection	None		Equipped
Ink ribbon	Purple, Cassette		
Power supply	AC 100/120/230V DC 7V	Rechargeable internal battery	AC 100/120/230V DC 7V
Power consumption	7VA		
Weight	0.4kg		
External dimensions (W x D x H)	106 x 180 x 88mm		
Operating temp. range	5~35°C		
Storage temp. range	-20~60°C		
Reliability	MCBF 1.0 million lines (40 columns)		
Safety standard	FCC class A, TUV-GS, CE marking		

Japan CBM Corporation

Information Systems Division
 5-68-10 Nakano, Nakano-ku, Tokyo, 164-0001 Japan
 Tel: (81)-3-5345-7540
 Fax: (81)-3-5345-7541
<http://www.jcbm.co.jp/>
 e-mail: info-sys@jcbm.co.jp