KDC250 Laser Barcode Data Collector

A New Wave in Auto-ID

The KDC250 enables diverse mobile Auto-Identification applications for collecting and storing barcode data.

A built-in display eliminates blind erroneous data collections and enables interactive data collection processes.

It has an easy-to-replace rechargeable battery that can recharge from any USB Port.

With the optional 4MB of on-board memory it can store over 100,000 product records, memory shortages are also no longer a problem.

All KDC® products come with FREE KTSync® software (includes keyboard wedging, application generation, DB look up and inventory management features) and FREE SDK (includes technical support from our top engineers and development







ADVANCED FEATURES

- 48 Channel GPS Receiver
- Class2 Bluetooth® with HID and SPP Profiles
- Bright 1" OLED Display
- Rechargeable Li-Ion Battery
- Stores 100,000+ Product Records
- KTSync® with Keyboard Wedging, Application Generation, DB Look up and Inventory Management features

Transportation

- Retail
- Transportation
- Field Services
- Warehouse
- Healthcare
- Hospitality
- Event Technology



KDC250 Specifications

Hardware Specifications

Physical Characteristics

Size: 1.45"x 3.26"x 0.82" (37mmx83mmx21mm)

Weight: 2.0 oz. (57 grams)

Electrical Characteristics

Battery: Lithium-Ion (3.7V DC, 650mAh)

Charging: Via USB connector

Typical Operating Current: 170mAh@3.3V

Scanning Performance

Scan Rate: 100 scans/sec

GPS

PT9250 48 channel GPS Receiver

User Environment

Drop Spec: 4 feet (1.22m) with Rubber Case

Operating: $32^{\circ}F$ ($0^{\circ}C$) ~ $113^{\circ}F$ ($45^{\circ}C$) **Storage**: $-4^{\circ}F$ ($-20^{\circ}C$) ~ $113^{\circ}F$ ($45^{\circ}C$) **Humidity**: 5% ~ 85% (noncondensing)

Interfaces

Bluetooth® V2.1+EDR, Class 2, HID/SPP USB to Serial (Ultra mini USB port)

Functionality

Memory Flash ROM: 256KB Program, 4MB User Data

Memory RAM: 64KB

Microprocessor: ARM7, 32 bits

Real-time Clock: Quartz RTC for timestamp

Symbologies

EAN, UPC, Code 39, Code 93, Code 128, Codabar, Interleaved 2 of 5, GS1-128, Code 3 of 5

Wedging & Synchronization

- Store to a file or transfer to the application
- Keyboard wedge function
- Add-on prefixes and suffixes
- Barcode option selection

Application Generation

- SDK for PC, Pad and Smartphone application
- Application generation tool
- Database lookup feature
- Inventory management feature

Regulatory Conformance

Laser Safety - IEC / CDRH Class II EMC - CE, FCC, MIC, TELEC

Models

KDC250, KDC250M, KDC250i, KDC250iM, KDC250G, KDC250GM, KDC250Gi, KDC250GiM

Package Contents

1 Data Collector with rechargeable battery

1 USB cable, 1 Lanyard, 1 Software CD,

1 Protective Boot, optional Finger Trigger Glove





For more information, contact us at:

Goodson Imports Pty Ltd 9 Liberty Road Huntingwood NSW 2148 Australia Representation in all main States & New Zealand

Ph: 1300 921 132 Fax 02-8875 4588 email: sales@goodson.com.au www.goodson.com.au



