

PS-3315E

POSIFLEX

Slim and Flexible

Streamlined design equips with a foldable base; PS-3315E provides users with unmatched flexibility to adjust the screen to a height and angle depending on the application.

Expandable and Neat

Designed to better manage peripheral connectivity by separating a full set of ports into the top of the terminal top and the base, PS-3315E ensures neat, reliable peripheral cabling.

| Specification | PS-3315E |
|----------------|--|
| Processor | Intel J1900 processor, 2.00GHz/2.42GHz (Burst), 1M cache |
| System Memory | DDR3L 1333MHz SO-DIMM x 1, max. 4GB |
| Storage Device | 1 x SATA + 1 x eMMC connector, 64GB SATA SSD default |
| Power Supply | 12V/30W |
| OS Support | Windows 10 IoT/Windows Embedded 8.1 Industry/Windows 7/PCSRReady 7/Linux per request |

| Display | |
|----------------|------------------------------------|
| LCD Display | 15" TFT LCD, 1024 x 768 resolution |
| Touch Function | 5-wire resistive touch |

| Connectivity | |
|-------------------|---|
| LAN Port | 10/100/1000Mb x 1 |
| Serial Port | 3 x DB9 + 1 x RJ45, 5V/12V support on all COM ports |
| Parallel Port | 1, via optional conversion cable |
| UPS Port | N/A |
| Standard USB Port | 5 |
| PS/2 Port | 1, via optional conversion cable |
| Display Port | VGA x 1, 12V support for Posiflex monitors |
| CR Port | 1, control 2 CR via optional Y-cable |
| Audio | Buzzer only |
| WiFi | Optional internal mini-PCIe WiFi module with PIFA Antenna |

| Physical Dimension | |
|-----------------------------|-------------------|
| Dimension (W x D x H in mm) | 372 x 320 x 252.7 |
| Weight (N.W. in Kg) | 5.86 |

| Environment | |
|---------------------|--|
| Operation Condition | 0°C - 40°C, 20%RH - 90%RH [Equipped with HDD]; 0°C - 50°C, 20%RH - 90%RH [Equipped with SSD] |
| Storage Condition | -20°C - 70°C, 10%RH - 90%RH |

| Options | |
|------------------|---|
| SA-105 | Side Attachment for PS Series with 3 track MSR |
| SA-205 | Side Attachment for PS Series with iButton |
| SA-305 | Side Attachment for PS Series with support for 3 track MSR, RFID and Finger Print Sensor |
| SA-405 | Side Attachment for PS Series with support for 3 track MSR, 3G dongle and Finger Print Sensor |
| SA-505 | 3-in-1 attachment with MSR (default), RFID & iButtonsupport for 15"/17" XT series & 15"/15.6" PS series |
| LM6807U/LM6810U | 7" 800 x 480 / 10" 1024 x 768 rear-mount 2nd display for PS series (USB interface) |
| PD-2609UE | 2 x 20 VFD, rear-mount, USB with Virtual COM support |
| PD-360UE/PD-360R | 2 x 20 LCD, rear-mount, USB with Virtual COM support (PD-360UE)/RS232(PD-360R) |
| PD-6807U | 7" color LCD graphical line display, rear-mount (USB interface) |
| KP-500 | 40-key dynakey attachmentwith MSR or RFID option for 15"/17" XT series & 15"/15.6" PS series |

* The product information and specifications are subject to change without prior notice.
* Please refer to the web site for more attachment options.

US Patent 9004436



PS-3315E Best Value Fanless POS Terminal

PS-3315E is a 15" touch screen fanless POS Terminal with all the essential functions and capabilities to satisfy businesses of all sizes, and represents one of the best value choices in the entry-level POS Terminal segment.



Design and Manufacturing in Taiwan by Posiflex Technology Inc.
The product information and specifications are subject to change without prior notice.

2016Q1

POSIFLEX

POSIFLEX TECHNOLOGY INC.
No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan
Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw
Fax : +886-2-2299-1819 www.posiflex.com

Authorised Australian & New Zealand Distributor:
Goodson Imports Pty Ltd
142 Wicks Road
Macquarie Park NSW 2113
Offices in all main States and New Zealand
Ph: 02-8875 4544 Fax 02-8875 4588
www.goodson.com.au