

FORTIS XP-3000 Series



Clear LED indicator panel



Printer

3" thermal printer (60mm/sec)



MSR

2 or 3 tracks & JIS-II



XP-3000 Series applies Intel Pine View technology; fast speed Ethernet as well as plenty of connects ports of USB, Serial, VGA and CR ports. It also integrated with thermal printer, touch screen and MSR, as well as designed with gorgeous appearance and small footprint for counter space saving.

The small and fully integrated system is suitable for many kinds of segments, such as general retailer, hospitality and restaurant. In addition, XP-3000 series terminal assist small and medium business to serve customer effectively, speedy and precise.

Features

- All-in-one integrated system with touch screen, thermal printer and MSR that cleans up the counter space of all the unsightly wirings.
- Fan-free design with aluminum die casting structure ideally suited for both harsh and quiet environment.
- Intel Pineview technology offers low power consumption, which in turn lowers the cost of ownership due to the lower energy cost.
- 3" thermal printer featuring "One-button cutter blade retract" design. It is achieved by simply pushing the button to open the paper cover and automatically retract the cutter blade for easy paper jam removal.
- Built-in emergency UPS support to avoid sudden loss of power during transaction.
- High quality, rock solid build & design with ease of maintenance and serviceability in mind.



Real mount customer pole display



12" 2nd LCD Display or touch LCD Display with attachment SD-300



Specification	XP-3012H	XP-3015H
Processor	Pine View-D SC 1.66GHz / 512K Cache CPU, Upgrade to Pine View -D DC 1.66G / 1M Cache CPU (Dual Core)	
System Memory	DDR2 667 MHz,SO-DIMM x 1, max 2 GB, default 1GB	
Storage Device	2.5" SATA HDD or SSD Kit (optional)	
Power Supply	12V DC power adaptor, 80W	
Audio	Buzzer Only	
OS support	Windows XP Pro / WEPOS / POSReady / Win 7 / Linux	
Display		
LCD	12" TFT LCD, 1024x768 resolution	15" TFT LCD, 1024x768 resolution
Touch Function	Resistive, 5-Wire, USB Interface	
Brightness Control	By Digital Push Botton	
Tilt Adjustment	From 14° to 55°	
Connectivity		
LAN Port	10 / 100 / 1000 Mb	
Serial Port	DB9 x2, RJ-45x1 (RJ-45 to DB9 Cable Optional),with 5V support on COM2/COM3	
PS/2 Keyboard	Optional by internal cable	
UPS Port	Yes, Battery Optional	
Standard USB Port	4	
VGA Port	D-SUB, 15 Pin,with 12V power for Posiflex LCD Monitor	
CR Port	1, Control 2 CR	
Printer		
3" Thermal Printer	60mm/sec, 80mm paper width	
Cutter	Auto cutter	
Physical Dimension		
Dimension (W x D x H in mm)	325 X 386.2 X 298.1	375 X 386.2 X 395
Weight (N. W. in kg)	6.24	6.83
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
Options		
MSR	Integrated, 2 or 3 tracks and JIS-II	
PD-2606U	VFD, 2x20, rear mount	
PD-330U	LCD, 2x20, rear mount	
PD-76X4	240x64 dot Graphics LCD, default 200mm pole	
PD-2605 / PD-2605U	VFD, 2x20, default 200mm pole	
PD-309 / PD-309U	LCD, 2x20, default 200mm pole	
SSD	8G minimum	
LM/TM-2212	12" 2nd LCD Display or touch LCD Display with attachment SD-300	
UPS Battery	2300mAh / 12V	

❖ The product information and specifications are subject to change without prior notice.

2010 V.01

Posiflex Technology, Inc.

6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan
 Tel: 886 2 2299-1599 Fax: 886 2 2299-1819
 sales@posiflex.com.tw www.posiflex.com

Australian Distributor:
 Goodson Imports Pty Ltd
 142 Wicks Road
 North Ryde NSW 2113
 Offices in all main States and New Zealand
 Ph: 02-8875 4544 Fax 02-8875 4588
www.goodson.com.au

