



Tamper Resistant and Fanless Multi-touch PC tile **eTILE 19M Value FanFree**



The Etile 19M Value FanFree is a fanless 18.5" all-in-one touch display. Developed with POS in mind; this multi-touch PC tile can be integrated in various retail settings. Combining esthetically pleasing design with practical features such as an USB with power makes this eTILE the perfect retail solution.

The eTILE 19M Value FanFree includes the following features:

- + A fanless, silent all-in-one interactive display
- + USB with power for auxiliary devices such as scanners and printers up to 1A per USB connection
- + Modular RJ50 connector for RS232 connection (voltage configurable)

eTILE 19M Value FanFree



Model name		WT19M-FB
Feature		Ultra-thin, all-in-one touch display
Dimension	W x H x D (mm)	448 x 284 x 30 mm
	W x H x D (inch)	17,6 x 11,1 x 1,18 inch
Weight (Kg/Pound)		5 kg / 11 lbs (N.W.)
CPU	Type	Intel® N2930
Memory		Supports: 2 x DRIII SO-DIMM (Max 8G) Default 2Gx1
Graphics		Intel® HD Graphics series, depending on the CPU
Audio		Realtek ALC269-VC Digital Multichannel HDMI
Expansion	Mini Card Slot	x2 (Full size, one supports mSATA)
LAN		Realtek RTL8111G Ethernet 10/100/1000
Storage		Supports 2.5" SATA III HDD/SSD (HDD enclosure not included) and mSATA Default 32G mSATA SSD
LCD	Display size	18.5"
	Resolution	1366x768 /16:9
	Brightness	250 Nits
Touch Panel		PCT (Project Capacity Touch) (10 point touch) Pencil hardness: 7H per ASTM D3363
Adapter		90W (19.5V, 4.74A) AC Adapter

System I/O	DC 12V-19,5V input	x 1
	HDMI (mini) out	x 1
	USB 2.0 port (1A)	x 4
	RJ45 LAN Jack	x 1
	RS232 Serial RJ50 (voltage configurable)	x 4
	Audio Line-in	x 1
	Audio Line-out	x 1
Watchdog Timer		1 sec ~255sec
IP Grade		Front panel IP65 dust- & waterproof
Accessories		90W power adapter Wall mount kit Power cord
Security		Hidden Keypad Secure Cable Cover
Environment		
MTBF		50,000 hours
Storage Condition		-20~60°C (-4~140°F), 90% RH (40°C non-Condensing)
Operating Temperature		0 ~ 40°C (32 ~ 104°F)
Operating Shock		8G, half sine, 11ms duration, 3Axes, 6Direction
Operating Vibration		0.6Grms, random, 10~500Hz, X,Y,Z 3Axes, 0.5hr/Axis



Authorised Australian & New Zealand Distributor:
 Goodson Imports Pty Ltd
 9 Liberty Road, Huntingwood NSW 2148
 Representation in all main States and New Zealand
 Ph: 02-8875 4544 Fax 02-8875 4588
www.goodson.com.au

The specifications depicted may be subject to change without prior notice.
 All trademarks are copyright of their respective owners. © AOPEN Inc.