



Speedy...Silent...Smart...Service...SAM4S..

## **ELLIX 10**













### Thermal receipt printer

This durable receipt printer ELLIX 10 is designed for any retail environment. "You will be satisfied with ELLIX 10's all of features and performances while the unique qualities and styles of ELLIX 10 make your business environment more convenient."

#### ELLIX 10 can meet all your basic needs for receipt printing.

- ELLIX 10's maximum printing speed is 75mm/sec.
- ELLIX 10 has high reliability as MCBF 30,000,000 lines.
- ELLIX 10 completely comes with the industry's standard emulations, so it's ready to plug and play with your current application.
- ELLIX 10 has intuitive paper loading (drop-in type), RS-232C interface and a convenient cover open method.
- ELLIX 10's ivory and dark grey color combination fits well in any environment.
- It is designed to be more simple and comfortable for using.



(2 inch)



## **ELLIX 20**

# New generation thermal receipt printer
























When you meet the ELLIX 20, you feel free about the speed. This high speed receipt printer, ELLIX 20 has the printing speed 220mm/sec (max) and there's no need to keep customers waiting.

SAM4S offers you the ELLIX 20, it's the most advanced receipt printer. And also you can choose the paper width in either 58mm or 80mm.

- ELLIX 20's maximum printing speed is 220mm/sec.
- It is incredibly reliable with MCBF rate of 70,000,000 lines.
- ELLIX 20 works with 3" thermal paper, in addition, if you put a separator inside, you can also use 2" thermal paper.



(3 inch)



# ELLIX 20 provides advanced features for convenience!



#### → Superb printing speed

- ELLIX 20's maximum printing speed is 220mm/sec
- ELLIX 20's 2 color maximum printing speed is 100mm/sec



#### → Various Interfaces

- Serial (RS-232C/ RS-485) Ethernet
- Parallel (IEEE-1248) Bluetooth
- USB Wi-Fi



#### → High Reliability

- It is incredibly reliable with MCBF rate of 70,000,000 lines
- TPH is 1x108 Pulse, 100 KM
- Auto cutter standard (1,500,000 cuts)



#### → 2 color printing

• ELLIX 20 is available for thermal printing in Black/Red or Black/Blue



#### → Logo/ Coupon / Barcode printing

• ELLIX 20 is available to keep your company logo, coupon and barcode in storage and print-out



#### → Easy paper loading

- ELLIX 20's paper loading is very easy and trouble-free when you run out of paper, you can just drop a new roll
- ELLIX 20 has paper near-end sensor



# Compact Design



#### → Outstanding Design


- ELLIX 20 is designed for flexibility
- ELLIX 20 is possible to use WALL MOUNT or STAND at a kitchen, counter and any other market surroundings
- ELLIX 20 is flexible for 2" and 3" thermal paper





Interface

Barcode





2 inch (58mm)-separator 3 inch (80mm)



Stand Wire arrangement

#### ■ SAM4S Thermal Receipt Printer Specification

MODEL NAME

#### ELLIX 10 (2" thermal)

#### **ELLIX 20 (3"/2" thermal)**







Printing Method			
	Mono Paper 80mm		
Printing speed	Mono Paper 58mm		
Resolution	Two Color Paper		
Resolution	Font A		
Print Font	Font B		
		Font A	
	Column capacity	Font B	
Print Pont	Character size	Font A	
		Font B	
	Character Set		
Paper	Loading		
	Dimension		
	Thickness		
Auto Cutter		1	
Reliability	Mechanism(MCBF) TPH		
	Auto cutter		
Barcode	1		
Driver			
Drawer Port			
Interface			
Power Supply			
Sensor	Paper Near End Sensor		
	Paper End Sensor		
Overall Dimension (w	,		
Mass(Approx.)	SET only With Packing		
Certificate	EMC		
	Safety		
Body Color			
Emulation			
Two Color Printing			
Statistic function			
0	Temperature	Operating	
		Storage	
On a making a Campitition	Humidity	Operating	
Operating Condition	Humidity	Storage	

Direct thermal line printing	
- Max. 75mm/sec (20 line/sec)	
-	
200 dpi	
12*24	
9*17	
32	
42 1.5(W)*3.0(H) mm	
1.12(W)*2.12(H) mm	
95 Alphanumeric, 37 International,	
128*11 Graphic, Korean	
Drop-In Type	
Max .58.0 x Ø 70.0mm	
0.06~0.08 mm	
Guillotine Type(option)	
30,000,000 lines	
1x10 <sup>8</sup> Pulse, 50 KM	
1,000,000 cut	
UPC-A, UPC-E, EAN8, EAN13, Code 39,	
Code 93, Code 128, ITF, CODABAR	
Windows Driver	
OPOS Driver	
* RS-232C 1 port SERIAL	
CMDC Adenter/INL AC 00, 27/1//OLIT, DC 0V	
SMPS Adaptor/IN: AC 90~264V/OUT: DC 9V Option	
YES	
118.0(W)x200.0(L)x111.0(H) mm	
1.2 Kg	
2.2 Kg	
FCC class A, CE marking	
TUV/GS,CE,CB,cTUVus	
IVORY & Dark Grey or All Dark Grey	
Epson, Star	
none	
none	
5°C ~ 45°C	
-10°C ~ 50°C	
10% ~ 90%	
10 ~90%(RH)	
:Except for Paper	
1.Auto Cutter + Paper near end	

Direct thermal line printing
Max. 220mm/sec(52 line/sec)
Max. 150mm/sec(36 line/sec)
Max. 100mm/sec (24 line/sec)
180 dpi
12*24
9*17
42(80mm) / 30(58mm)
56(80mm) / 40(58mm)
1.69(W)*3.38(H) mm
1.26(W)*2.39(H) mm
95 Alphanumeric, 37 International,
128*11 Graphic, Korean
Drop-In Type
Max. 58.0/80.0 x Ø 83.0mm
0.06~0.08 mm
Guillotine Type
70,000,000 lines
1x10 <sup>8</sup> Pulse, 100 KM
1,500,000 cut
UPC-A, UPC-E, EAN8, EAN13, Code 39,
Code 93, Code 128, ITF, CODABAR, PDF417
Windows Driver
OPOS Driver
2 PORT (+24V)
* RS-232C,IEEE-1284,RS-485
* USB, ETHERNET,Wi-Fi,Bluetooth
SMPS Adaptor/IN: AC 90~264V/OUT: DC 24V
YES(STAND and WALL)
YES
145.0(W)x200.0(L)x140.0(H)mm
1.7 Kg
2.9 Kg
FCC class A, CE marking
TUV/GS,CE,CB,cTUVus
IVORY & Dark Grey or All Dark Grey
Epson, Star
YES
YES
5°C ~ 45°C
-10°C ~ 50°C
10% ~ 90%
10 ~90%(RH)
:Except for Paper
1.Wall mount kit
2.Paper separator(58mm)
3.Kitchen Bell

<u>S</u> p e e d y . . . <u>S</u> i l e n t . . . <u>S</u> m a r t . . . <u>S</u> e r v i c e . . . <u>S</u> A M 4 S . . .



#### **Shin Heung Precision Co.,Ltd.**

SEOUL OFFICE (SAM4S ECR & POS System department)

FLAT C-911, WOORIM LION'S VALLEY, 371-28 GASAN-DONG, GEUMCHEON-GU, SEOUL 150-834, KOREA

TEL: + 82 2 2101 9615-9621 FAX: + 82 2 2101 9690 E-mail: webmaster@sam4s.com http://www.sam4s.com

(Specifications are subject to change without notice 2005 ELLIX 10\_20-1)

Distributed by :