

## PE-292 NFC

2.9 inch E-paper + NFC + LED

The PE-292 is the next generation powered ESL with a high resolution fully graphical, e-paper based display and integrated NFC and LED. Perfect for dynamic customer interaction in stores and for payment purposes.



## Highlights

- Enables on-demand, real-time pricing, promotions and product information
- Reduces waste and labor costs and minimizes errors
- Integrated NFC chip allowing various payment methods
- Incorporates RGB LEDs and sound feedback to attract attention
- Externally powered via **rail system**, for more information, check the accessories brochure of the PE-range
- 100% display content flexibility and centralized administration of all devices and content via the Opticon ESL Server Software
- Bi-Stable display, so the image will remain on the display even after power is disconnected
- High contrast display allows scanning of barcodes off the display using a standard barcode scanner
- Display can be remotely updated via bidirectional communication using the Opticon Base Station
- A wide variety of secure, durable and esthetically pleasing display shelf mounting options and accessories for in-store shelving are available Extremely low power consumption
- 2.4 Ghz, 802.15.4 based protocol



# PE-292 NFC

## Product Specifications

### Operation

CPU: 8-bit MCU

Clock frequency: 32 MHz

### Memory

Internal ROM: 256 KB

Internal RAM: 8 KB

### Operating indicators

Number of LEDs: 10

Buzzer: programmable frequency and volume

### Communication

Range: typical 25 meter indoor; 100 meter open-field

Radio frequency: 2.4 GHz (2405 - 2480 MHz)

Radio transmission speed: up to 250 kbps

Protocol: IEEE 802.15.4 based

No. of PE-292 ESL's per base station: 1,500

### Power

Power supply: dedicated power rail, 5-12V

Power consumption: 0.68W per ESL (max.)

### Display

Size: 2.9", 296 x 128 pixels (WxH), black and white

Active area: 66.9 x 29.06 mm (WxH)

Pixel Pitch: 112 dpi

### NFC

Frequency: 13.56MHz

Protocols: ISO/IEC 14443A/MIFARE/NTAG

### Durability

Temperature in operation: 0 to 40 °C / 32 to 104 °F

Temperature in storage: -20 to 60 °C / -4 to 140 °F

Humidity in operation: 20 - 85% (non-condensing)

Humidity in storage: 20 - 85% (non-condensing)

### Physical

Dimensions (WxHxD): 92.3 x 42.2 x 11.3 mm /

3.63 x 1.66 x 0.44 in

Mounted on a dedicated power rail: 12.1 mm thickness

Weight: Ca. 28.6 g / 1.0 oz

### Regulatory & Safety

Product compliance: FCC, RoHS, EN 60950-1, IEC 60950-1, EN55022, EN55024, WEEE

### Accessories

For dedicated and universal accessories, check online the Accessories brochure of the PE-Range.

Australian Distributor: Goodson Imports Pty Ltd  
Representation in all main States and New Zealand,  
Head Office: 9 Liberty Road, Huntingwood NSW 2148, Sydney Australia  
Ph: 02-8875 4544 Fax 02-8875 4588, [www.goodson.com.au](http://www.goodson.com.au)