

POSIFLEX



Taking Space Saving to Extremes

HS-3510W-G2/3512W-G2/3514W-G2

Space Saving All-in-one POS Terminal

HS-3510W-G2/3512W-G2/3514W-G2

The HS-3500-G2 Series is a whole new generation of high-end all-in-one POS terminal, packing innovativeness and functionality in compact design with stylish look. It is the perfect fit for retail businesses where space is at premium.



10"



12"



14"

Innovative All-in-one Terminal

This compact all-in-one 10"/12"/14" touch POS now comes with a detachable receipt printer for easy maintenance. Add an optional 2D barcode scanner while the printer is on board, making the HS-3500-G2 Series the most well-rounded all-in-one POS terminal in the market.

Integrated Design with Advanced Manageability

The HS-3500-G2 Series integrates the most widely used peripherals including 3" thermal printer, MSR, fingerprint sensor, 2D barcode scanner and 2nd customer display to support your daily POS operation. The detachable modularized design allows quick access to the components, enabling fast and easy service and upgrades.



Detachable Receipt Printer



Aesthetics

Dressed from head to toe in timeless black or white color, the only trend that never goes out of style, and with stylish touches added throughout, the HS-3500-G2 Series is not just a piece of machinery, it is an elegantly crafted piece of art that looks right at home in any store decoration.



2D Barcode Scanner



Optional Built-in MSR
Fingerprint Sensor
and RFID Reader

HS-3510W-G2/3512W-G2/3514W-G2

Specification	HS-3510W-G2	HS-3512W-G2	HS-3514W-G2
Processor	Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache		
System Memory	DDR4 SO-DIMM x 2, max. 32GB		
Storage Device	M.2 connector [supporting AHCI mode] x 2		
TPM	Yes, TPM 2.0		
Power Supply	24V/100W		
Built-in Printer	3" detachable printer w/ auto cutter, 250 mm/sec (max.)		
Built-in WiFi	N/A		
OS Support	Win 10 IoT		

Display & Touch

LCD	9.7" TFT LCD	12" TFT LCD	14" TFT LCD
Resolution	1024 x 768	1024 x 768	1366 x 768
Touch	True-flat PCAP touch with multi-touch support		

I/O & Expansion

Serial Port	3, DB9 x 2 + RJ45 x 1, 5V/12V support on all COM ports		
Parallel Port	Yes		
Standard USB Port	4, USB 3.0 x 1 + USB 2.0 x 3		
OTG USB	N/A		
LAN Port	10/100/1000 Mb x 1		
Display Port	VGA x 1, 12V support for Posiflex monitors		
CR Port	1, control 2 CR via optional Y-cable (printer driven), supporting 24V cash drawer		
PS/2 Port	Yes		
Audio	Line-Out x 1		
Expansion Slot	M.2 slot x 1		

Physical Dimension

Dimension (W x D x H in mm)	244.5 x 198 x 434	297 x 198 x 473	371.5 x 198 x 473
Weight (N. W. in kg)	4.4	5.5	6

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH		
Storage Condition	-20°C - 70°C, 10%RH - 90%RH		

Built-in Options

WiFi	M.2 WiFi/BT module		
MSR	3 tracks ISO or JISII (HID/VCOM selection)		
Fingerprint Sensor	Optical type		
RFID Reader	Support MIFARE Ultralight and Classic 1K card (HID/VCOM Selectable)		
Scanner	2D barcode scanner		
iButton	Yes (cannot coexist with Fingerprint Sensor)		
4G / LTE Communication	Single SIM slot, selected band support		

Attachment Options

POS Monitor	Non-touch TFT LCD: 7"/9.7"/12.1"; PCAP touch TFT LCD: 9.7"		
Line Display	2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display;		

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc. *The product information and specifications are subject to change without prior notice.
*Please refer to the website for more attachment options.

Certifications	      	EN20230324V3
 <div> <p>POSIFLEX TECHNOLOGY, INC.</p> <p>No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan</p> <p>Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw</p> <p>Fax : +886-2-2268-5388 www.posiflex.com</p> </div> <div> <p>Authorized Distributor / Reseller</p> </div>		