

# **Xenon 1902**

# Wireless Area-Imaging Scanner

Xenon 1902, Honeywell's sixth-generation of area-imaging technology, is redefining the standard for hand-held scanners. Featuring a custom sensor that is optimized for bar code scanning, Xenon 1902 offers industry-leading performance and reliability for a wide variety of applications that require the versatility of area-imaging technology plus the freedom of Bluetooth® wireless connectivity.

Powered by Adaptus® Imaging Technology 6.0, Xenon 1902 delivers superior bar code scanning and digital image capture. Xenon 1902 incorporates a revolutionary decoding architecture and a custom sensor, enabling extended depth of field, faster reading, and improved scanning performance on poor quality bar codes. From high density linear to 2D bar codes found directly on the screen of a mobile device, Xenon 1902 decodes virtually all bar codes with ease.

Xenon 1902 incorporates a Bluetooth Class 2, v2.1 radio, enabling unrestricted movement up to 33 feet (10m) from the base. Honeywell's Shift-PLUS™ power management system provides up to 14 hours of battery life, maximizing productivity. For added convenience, a paging system helps locate misplaced scanners.

A new space-saving design that mounts critical components on a single board eliminates the need for connectors. A more reliable design with fewer components minimizes downtime and improves serviceability, resulting in increased productivity. Its small form factor ensures that the Xenon 1902 fits well in nearly any sized hand, reducing fatigue.

Built with durability in mind, Xenon 1902 can withstand up to 50 drops to concrete from 6 feet. An IP41-rating provides added protection. With a solid-state design backed by a three-year warranty, Xenon 1902 is constructed to deliver years of uninterrupted performance.



### **Features**

- Wireless Connectivity: Bluetooth Class 2, v2.1 radio enables movement up to 33 feet (10m) from base, reduces interference with other wireless systems, and lowers total cost of ownership by allowing up to seven imagers to communicate to a single base
- Long-Lasting Lithium-lon Battery: Powers up to 50,000 scans per full charge, ensuring maximum uptime
- Flexible Power Management: Allows user to limit radio power output of scanner, minimizing the likelihood of interference with other devices
- Image Processing Software: Offers advanced editing functionality—cropping, brightening, rotating, sharpening and more—to produce high-quality digital images
- TotalFreedom™2.0: Second-generation development platform enables the loading and linking of multiple applications on the scanner to enhance image processing, decoding or data formatting functionality, eliminating the need for host system modifications
- Provides a quick and convenient solution for IT administrators seeking to manage all scanners within their network from a single remote location

## **Xenon 1902 Technical Specifications**

Wireless				
Radio/Range	2.4 to 2.5 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth v2.1; Class 2: 10 m (33') line of sight			
Data Rate (Transmission Rate)	Up to 1 Mbit/s			
Battery	1800 mAh Li-ion minimum			
Number of Scans	Up to 50,000 scans per charge			
Expected Hours of Operation	14 hours			
Expected Charge Time	4.5 hours			
Mechanical/Electrical				
	Scanner	Charger/Communication Base		
Dimensions (LxWxH)	104 mm x 71 mm x 160 mm (4.1" x 2.8" x 6.3")	132 mm x 102 mm x 81 mm (5.2" x 4" x 3.2")		
Weight	214 g (7.5 oz)	179 g (6.3 oz)		
Operating Power (Charging)	N/A	5 W (1A @ 5 V)		
Non-Charging Power	N/A	0.5 W (0.1A @ 5 V)		
Host System Interfaces	N/A	USB, Keyboard Wedge, RS232, IBM 46xx (RS485)		
Environmental				
Operating Temperature	0°C to 50°C (32°F to 122°F)	Charging: 5°C to 40°C (41°F to 104°F) Non-Charging: 0°C to 50°C (32°F to 122°F)		
Storage Temperature	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)		
Humidity	0 to 95% relative humidity, non-condensing	0 to 95% relative humidity, non-condensing		
Drop	Designed to withstand 50 1.8 m (6´) drops to concrete	Designed to withstand 50 1 m (3.3') drops to concrete		
Environmental Sealing	IP41	IP41		
Light Levels	0 to 100,000 lux (9,290 foot-candles)	N/A		
Scan Performance				
Scan Pattern	Area Image (838 x 640 pixel array)			
Motion Tolerance	Up to 610 cm/s (240 in/s) for 13 mil UPC at optimal focus  (HD): Horizontal: 41.4°; Vertical: 32.2°  (SR): Horizontal: 42.4°; Vertical: 33°  (ER): Horizontal: 31.6°; Vertical: 24.4°			
Scan Angle				
Print Contrast				
Pitch, Skew				
Decode Capabilities	Reads standard 1D, PDF, 2D, Postal and OCR symbol *Note: Decode capabilities dependent on kit configurations.			
Warranty	3 year factory warranty (Note: battery warranty is 1 year)			

1.0 mm Max output: both mill tell settles—1 set 2 (2007) Fuse dustation of 15 Sissec. Complex with 21 CFR 104/30 and 164(11 sacret for deviations gunuarit to Laser Notice No. 36, dated June 24, 2007.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies

Typical Performance\*

\*\*Data Matrix (DM)

1912g laser-aimer model only

Extended Range (ER)

Narrow Width				
5 mil Code 39	0 mm - 104.1 mm (0" - 4.1")	27.9 mm - 134.6 mm (1.1" - 5.3")	94 mm - 203.2 mm (3.7" - 8.0")	
13 mil UPC	10.2 mm - 167.6 mm (0.4" - 6.6")	10.2 mm - 439.4 mm (0.4" - 17.3")	25.4 mm - 525.8 mm (1.0" - 20.7")	
20 mil Code 39	10.2 mm - 233.7 mm (0.4" - 9.2")	12.7 mm - 584.2 mm (0.5" - 23.0")	25.4 mm - 596.9 mm (1.0" - 23.5")	
6.7 mil PDF417	0 mm - 109.2 mm (0" - 4.3")	10.2 mm - 154.9 mm (0.4" - 6.1")	71.1 mm - 233.7 mm (2.8" - 9.2")	
10 mil DM**	0 mm - 127 mm (0" - 5.0")	12.7 mm - 190.5 mm (0.5" - 7.5")	63.5 mm - 287 mm (2.5" - 11.3")	
20 mil QR	10.2 mm - 190.5 mm (0.4" - 7.5")	15.2 mm - 383.5 mm (0.6" - 15.1")	17.8 mm - 482.6 mm (0.7" - 19.0")	
Resolution 1D Code 39	3 mil (0.076 mm)	5 mil (0.127 mm)	5 mil (0.127 mm)	
Resolution 2D DM**	5 mil (0.127 mm)	6.7 mil (0.170 mm)	7.5 mil (0.191 mm)	
*Performance may be impacted by bar code quality and environmental conditions				

Standard Range (SR)



#### For more information:

www.honeywellaidc.com

## **Honeywell Scanning & Mobility**

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com

### **Authorised Australian Distributor:**

Goodson Imports Pty Ltd 142 Wicks Road North Ryde NSW 2113 Offices in all main States and New Zealand Ph: 02-8875 4544 Fax 02-8875 4588 www.goodson.com.au

High Density (HD)



1902-DS Rev E 12/11 © 2011 Honeywell International Inc.