

EE-201

2 inch E-paper Display

HIGHLIGHTS

Extremely low power consumption

802.15.4 based protocol

2.4 GHz

IP 54



EE-201

Basic product specifications

OPERATION

CPU: CC2533-F96, 8051 core 8-bit MCU **CLOCK FREQUENCY:** 32 MHz

MEMORY

INTERNAL ROM: 96 kB **INTERNAL RAM:** 6 kB

OPERATING INDICATORS

RANGE: Typical 25 meter indoor; 100 meter open-field

DISPLAY

SIZE: 2", 200 x 96 dots (WxH), black and white **ACTIVE AREA:** 45 x 22 mm (WxH)

CONTRAST RATIO: 10:1 **PIXEL PITCH:** 111 dpi

COMMUNICATION

RADIO FREQUENCY: 2.4GHz (2405-2480 MHz) **RADIO TRANSMISSION**

SPEED: up to 250 kbps **PROTOCOL:** IEEE 802.15.4 based **NO. OF EE-201**

ESL's PER BASE STATION: 2500

POWER

BATTERY: 2x CR2450 **OPERATING VOLTAGE:** 2.0 - 3.3 V **NOMINAL VOLTAGE:**

3.0 V **USABLE TIME:** 7 years at room temperature (update frequency: 4 times per day, poll time 20 seconds)

DURABILITY

TEMPERATURE IN OPERATION: 5 to 50 °C / 41 to 122 °F **TEMPERATURE IN**

STORAGE: -20 to 60 °C / -4 to 140 °F **HUMIDITY IN OPERATION:** 20 - 60%

(non-condensing) **HUMIDITY IN STORAGE:** 20 - 60% (non-condensing)

PROTECTION RATE: IP 54

PHYSICAL

DIMENSIONS (W X H X D): 65.0 x 34.0 x 15.0 mm / 2.56 x 1.34 x 0.59 in

WEIGHT: Ca. 40 g / 1.4 oz (incl. battery)

REGULATORY & SAFETY

PRODUCT COMPLIANCE: FCC, RoHS, EN60950-1, IEC 60950-1, EN 55022, EN 55024, CE, REACH

Authorised Australian & New Zealand Distributor:
Goodson Imports Pty Ltd
142 Wicks Road
Macquarie Park NSW 2113
Offices in all main States and New Zealand
Ph: 02-8875 4544 Fax 02-8875 4588
www.goodson.com.au

