



PD-7600 Series

- Graphic STN LCD (liquid crystal display) in blue background with white backlight.
- Stand alone Pole Display for POS application.
- Four-line display with 30 Arabic letters or 15 Chinese characters per line.
- 240 by 64 dots for graphic display.
- Adequately sized characters for easy viewing (8.47 mm by 4.24 mm per digit).
- Long life and trouble free operation.
- Display contrast adjust buttons on front surface.
- 15°, 30° and 45° adjustable viewing angles.
- Display frame can rotate horizontally 270° freely.
- Supports ESC/POS commands.
- Simple installation.
- Serial (RS232) interface.
- Case color choices: ivory, black.
- MODELS, LANGUAGES & CODE TABLES
 - PD-7610: Simplified Chinese, GB-2312
 - PD-7620: Traditional Chinese, BIG-5
 - PD-7630: Arabic, Windows code page 01256 (with Arabic numerals addressed in <80> ~ <89> of code page 1)



PD-320

PD-2800

PD-2800 / PD-320

- PD-2800 is a bright two-line VFD (vacuum fluorescent display) display with 20 characters per line and combines with green or blue filter.
- PD-320 is a two-line LCD display with 20 characters per line
- Stand along customer pole display for Posiflex POS terminals.
- Easy-to-read large characters (9.03×5.25mm for PD-2800, 6.0×9.6mm for PD-320).
- Long life and trouble free design.
- Various command emulation modes selectable by DIP switch.
- Support 12 Code Pages of 128 characters each on PD-2800.
- Support 12 international character sets of 12 characters each on PD-2800.
- USB interface with RS-232 emulation for numerous applications without modify the software.
- UPOS 1.8 and is WEPOS ready supported.
- Euro dollar sign supported in USA/European font table.
- Selectable command emulation modes including PST and EPSON command emulation modes for PD-320.
- Composed of several members in the family for versatile applications as tabulated below.



PD-2600 Series

- Bright VFD (vacuum fluorescent display) with green or blue filter.
- Stand along pole display.
- Two-line display with 20 characters per line.
- Adequately large characters for easy viewing (9.03mm by 5.25mm).
- Long life and trouble free operation.
- 15°, 30° and 45° adjustable viewing angles.
- Total height 410mm.
- Display frame can rotate horizontally 270° freely.
- Various command emulation modes selectable by DIP switch.
- Support 12 Code Pages of 128 characters each.
- Support 12 international character sets of 12 characters each.
- Simple installation.
- Selectable between Serial (RS232) interface model and USB interface model.
- Supports UPOS 1.8 and is WEPOS ready.



PD-2300

- Bright green fluorescent display.
- Two-line display with 20 characters per line.
- Adequately large characters for easy viewing (9.03mm by 5.25mm).
- Long life and trouble free operation.
- Generous base best for freely stand alone.
- Two adjustable viewing angles.
- Pole height adjustable.
- Display frame can slide horizontally and rotate 360° freely.
- Brightness adjustable by software.
- Simple installation.
- Pole high adjustable.
- Selectable interface of Serial interface with pass through capability and USB interface.
- Multiple choices for power supply source.
- Support Euro dollar sign.



PD-300 Series

- Two - line LCD display with 20 characters per line.
- Dark blue character with yellow green back-light.
- Easy viewing characters (6.0mm by 9.66mm).
- Display area 143mm by 21mm.
- Euro dollar sign supported in USA/European font table.
- Selectable command emulation modes including PST and EPSON command emulation modes.
- Long life, trouble free and user friendly operation.
- Composed of several members in the family for versatile applications as tabulated below.