



TX-3100E / TX-3000E



TX-3100S-E / TX-3000S-E

TX-3100E / 3000E Series

Advanced Fan-Free POS System

Key Features

- ▶ Equipped with Intel Pine View Dual Core D525 1.8 GHz (TX-3100E series) and DDR3 memory
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Patented aluminum die casting design for efficient cooling
- ▶ Wide range of I/O supports for various applications
- ▶ Compact size and wall mount capability for easy space arrangement
- ▶ Rear cable cover for safety and neat outlook (Except TX-3100S-E / TX-3000S-E)

Specification	TX-3100E / 3100S-E	TX-3000E / 3000S-E
Processor	Intel Pine View D525 1.8 GHz / 1 M Cache CPU (Dual Core)	Intel Pine View D425 1.8 GHz / 512 K Cache CPU
System Memory	DDR3 800 MHz, SO-DIMM socket x 1, max 4 GB, default 1 GB	
Storage Device	2.5" SATA HDD or SSD (Optional)	
Power Supply	12V DC power adaptor, 60W	
Audio	Buzzer Only	
OS support	Windows XP Pro / WEPOS / POSReady / Win 7 / Linux	
Connectivity		
LAN Port	10 / 100 / 1000 Mb	
Serial Port	DB9 x3, RJ-45x1 (Optional RJ45 to DB9 cable) with 5V support on COM2/COM3/COM4 12V support on COM2/COM3	
PS/2 Keyboard	Yes	
Standard USB Port	4	
VGA Port	D-SUB, 15 Pin, with 12V power for Posiflex LCD monitor	
CR Port	1, control 2 CR	
Physical Dimension		
Dimension (W x D x H in mm)	270 x 253 x 86 (TX-3100E / TX-3000E) 270 x 200 x 86 (TX-3100S-E / TX-3000S-E)	
Weight (N. W. in kg)	2,29	
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
Options		
SSD	8 GB Minimum	
Wall Mounting Kit	WB-6812	
Certifications		



Posiflex delivers the fan-free TX-3100E / TX-3000E series as advanced POS systems.

The TX-3100E / TX-3000E series come with modern and technical sensation. Their trim outline strike an impression upon first sight, and the aluminum die casting are adopted to show a glimpse of fashion and also enhance the thermal solution. Inside their compact figure, the TX-3100E and TX-3000E series accommodate Intel Pine View D425 1.8GHz and Dual Core D525 1.8 GHz CPU respectively, 2.5" HDD or SSD and a variety of connectivity like LAN, Serial, PS/2, USB, VGA and CR ports.

The TX-3100E / TX-3000E series are flexible for space-sensitive retailers to deploy them.

Design and Manufacturing In Taiwan by Posiflex Technology Inc. 2011 TX30SQ2C
 ** The product information and specifications are subject to change without prior notice.

Authorized Reseller